



YTX9-BS

12Volt 8Ah

Specifications

Nominal Voltage(V) **12V**

Nominal Capacity

10 hour rate	(0.80A to	10.50V	8.00Ah
5 hour rate	(1.31A to	10.50V	6.56Ah
2 hour rate	(2.80A to	10.20V	5.60Ah
1 C	(4.80A to	9.60V	4.80Ah
2 C	(8.64A to	9.60V	4.32Ah

Weight Approx. 2.90 kg(6.39Lbs.)

Sealed and non-spillable AGM Battery

Maximum Discharge Current for

5 seconds: **120A**

Charging Methods at 25 (77)

Charging Voltage **14.4 to 15.0V**

Coefficient -5.0mv/ /cell

Maximum Charging Current : **2.40A**

Float Charging Voltage **13.50 to 13.80V**

Coefficient -3.0mv/ /cell

Operating Temperature Range

Charge **-15 (5) to 40 (104)**

Discharge **-15 (5) to 50 (122)**

Storage **-15 (5) to 40 (104)**

Charge Retention (shelf life) at 20 (68)

1 month **97%**

3 month **91%**

6 month **82%**

Case Material **ABS**

(UL94 HB flame retardant)

Terminal **Motorcycle Type A**



Dimensions

mm(inch)

